# WhisperKOOL<sup>™</sup>



### **Key Features**

- Advanced Digital Controller
- Dynamic Airflow
- Coated Evaporator Coil
- Front or Rear Power
- Condensation Reduction
- Single Piece Mounting Bracket



#### **Features**

The next generation in specialty cooling systems. The SC Series embodies the latest and greatest system design technologies in an all-new housing design. Developed upon feedback directly from customers and installers, the unit incorporates a variety of high end componentry at an affordable price point. The SC Series is a direct replacement for one of the most well known cellar cooling units, the XLT. Just like the series it replaces, the units come in 5 models that effectively cool a 350 to 2000 cu. ft. properly insulated environment. Designed for simple through-the-wall installation, the unit fits between standard wall studs and a single piece mounting bracket eliminates the need for a support shelf. The SC has a 30°F temperature differential. In order to keep your cellar at 55°F, the area the unit exhausts into should not exceed 85°F. This makes interior installation ideal for SC series units.

## **Specifications**

Model	2000i	3000i	4000i	6000i	8000i
Cellar Size (cu. ft.)	300	650	1000	1500	2000
dBA	Evaporator: 60 / Condenser: 60			Evaporator: 65 / Condenser: 65	
Dimensions	14.25"W x 15.75"H x 17.5"D			14.25"W x 22.5"H x 21.64"D	
Weight (lbs)	65	67	67	104	104
AMPS (starting/running)	28/2.7	32/4.9	32/4.9	36/10.3	36/10.3
Installation	Through-the-Wall				
Thermostat	Advanced Digital Controller				
Temp. Delta	30°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 85°F)				
Outside Venting	Not recommended unless exhaust environment will not exceed 85F				
Ducting Options	ONLY the exhaust side can be ducted using the optional ducting kit				
Warranty	2 year parts and labor / 5 year compressor				
Compliance	ETL Listed				

## **Optional Accessories**

Exhaust Ducting Kit, Exterior Grille